



ZD420c 4-Inch Thermal Transfer Printer

Unique and intelligent time-saving ribbon cartridge for fool-proof instant loading

If you need a fast 4-inch printer that is easy to use, easy to deploy and easy to manage, choose the leader of the class — the ZD420c. A new ribbon cartridge and more status icons maximize uptime by making using the printer easier than ever to use. With virtually every modern wired and wireless connectivity option and support for many printer languages, deployment is always fast and easy — just unplug your existing printer, plug in the ZD420c and you're back up and running. Add new connectivity and media handling options whenever you need them, right on site. Monitor and manage all your ZD420c printers from the cloud, for unsurpassed management simplicity. And our optional Zebra OneCare service maximizes the availability of your ZD420c printers with unmatched direct-from-Zebra support that covers everything — from worn out printheads to normal wear and tear. The ZD420c — when ease of use, flexibility and management simplicity matter.



Optional battery for cordless operation

The removable desktop battery power option makes it easy to transport the ZD420c printer on a cart for on-the-spot printing, reducing steps, increasing productivity and improving task accuracy. The battery housing mounts securely to the printer base and connecting the battery is as simple as snapping the battery into the housing. And the high-capacity battery can power it all for a full shift — the printer at maximum print speed, along with a peeler, cutter and keyboard.

Link-OS for unparalleled ease of management

With Link-OS, Zebra's unique printer software platform, you can easily deploy and manage one printer, a group of specific printers or all printers anywhere in the world via the cloud. And a quick tap of an NFC-enabled mobile device on the ZD420 provides access to Zebra's extensive knowledge base of how-to videos and more for fast issue resolution.¹

Get all the features you need today — and easily add the features you need tomorrow

The movable media sensor supports media with off-center black marks, die-cut notches or multiple labels across the width. The printer offers virtually every modern connectivity option, including USB, auto-sensing serial or 10/100 Ethernet, 802.11ac Wi-Fi, Bluetooth 4.1, plus simultaneous support for Wi-Fi and Ethernet. Easily add new communication or media handling options right on site, such as serial or Ethernet connectivity, a peeler and a cutter. Backwards compatibility with existing applications, formats and printer languages allows you to easily upgrade from your aging Zebra LP 2824 Plus — just plug in the ZD420c and you're back up and running. And with support for Zebra ZPL and EPL printer languages and many non-Zebra languages, it's easy to upgrade from competitive printers.

Easy to clean and sanitize healthcare model

Disinfectant-ready plastics and a sealed button interface make the ZD420c-HC easy to clean and disinfect — crucial in hospitals and clinics. The printer fits easily in space constrained pharmacies, labs and nurses stations. And a 300 dpi printing option ensures that even the small labels on specimen containers and prescriptions are highly legible.

Groundbreaking ease of use

The ZD420c is loaded with features that make it the easiest printer to use in its class. The ZD420c is the only thermal printer to offer a ribbon cartridge that takes just a few seconds to load, with fool-proof one way first-time every-time instant loading. The crypto chip in the ribbon lets you know when the ribbon needs replacing. And with five intuitive status icons — status, pause, data, supplies and network — your workers can see at a glance what to do to keep the ZD420c up, running and available.



The ZD420c — When ease of use, flexibility and management simplicity matter.
For more information, visit www.zebra.com/ZD420

ZD420c Specifications Chart

Standard Features	
<ul style="list-style-type: none"> Thermal Transfer print method ZPL and EPL programming languages 5 status icon, 3 button user interface USB 2.0, USB Host OpenACCESS™ for easy media loading Dual-wall frame construction ENERGY STAR qualified Real Time Clock 	
Physical Characteristics	
Dimensions	10.0 in. L x 8.0 in. W x 7.0 in. H 254 mm L x 202 mm W x 177 mm H
Weight	5.0 lbs./2.3 kg
Printer Specifications	
Resolution	203 dpi/8 dots per mm Optional 300 dpi/12 dots per mm Resolution can be factory installed or changed on site via accessory kits. Resolution can be changed from 300 dpi to 203 dpi, as well as from 203 dpi to 300 dpi.
Memory	512 MB Flash; 256 MB SDRAM
Maximum Print Width	4.09 in./104 mm for 203 dpi and 300 dpi
Maximum Print Speed	6 in./152 mm per second (203 dpi) 4 in./102 mm per second (300 dpi)
Media Sensors	Full width, moveable reflective/black mark sensor; multi-position transmissive/gap sensor
Firmware	ZPL II; EPL 2; XML; ZBI
Media Characteristics	
Maximum Label Length	39.0 in./991 mm
Maximum Label and Media Width	4.65 in./118 mm
Media Roll Size	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1), 2.0 in., (50.8 mm) and 3.0 in. (76.2 mm) using optional adapters
Thickness	0.003" (0.08mm) min.; 0.0075 (1905mm) max. (tear-off mode only)
Media Types	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receipt paper, and wristbands
Operating Characteristics	
Operating Temperature	40° to 105° F/4.4° to 41° C
Storage Temperature	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Electrical	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified; optional 2750 mAh battery

1. NFC Print Touch not available on all models.

Printer Supplies	
Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.	
Options and Accessories	
Media Handling	Field installable dispenser — label peel and present with label present sensor; field installable cutter
Communications	Field installable RS-232 auto-sensing Serial, DB-9 factory installed or field installable Ethernet — 10/100 internal; factory installed wireless radio: 802.11ac Wi-Fi and Bluetooth 4.1
Battery	Provides power to the printer to support a full shift of printing at maximum print speed; supports all media handling options
Keyboard Display Unit	ZKDU keyboard display units for stand-alone printing solutions
Mounting Plate	Optional accessory to secure ZD Series printers to countertops or shelves
Enclosed Power Supply	Attached power supply accessory for cord-free installation
Fonts/Graphics/Symbologies	
Barcode Ratios	2:1 and 3:1
1D Barcodes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Barcodes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
Fonts and Graphics	16 resident expandable ZPL II bitmap fonts, two resident scalable ZPL fonts, five resident expandable EPL2 fonts, native open-type font support, Unicode compliant. China units include SimSun simplified Chinese font 64 MB user available non-volatile memory, 8 MB user available SDRAM
Regulatory	
IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM	
Environmental Compliance	
Environment <ul style="list-style-type: none"> RoHS Directive 2011/65/EU; Amendment 2015/863 REACH SVHC 1907/2006 A complete list of product and materials compliance, please visit: www.zebra.com/environment	
Print DNA	
This printer is supported by our powerful Print DNA suite of applications, utilities and developer tools that give our printers better performance, simplified remote manageability, and easier integration. Print DNA features may vary by model and may require a Support Contract. For more information, please visit www.zebra.com/printdna	
Recommended Services	
Zebra OneCare Select	

The ZD420c is ideal in:

Light Manufacturing

- Agency labels/nameplates
- Product labels
- Apparel tags

Transportation & Logistics

- Asset labels

Healthcare

- Lab and specimen labels
- Asset labels
- Blood and IV bag labels
- Sterile services

Retail

- Asset labels
- Shelf labels
- Record labels

Government

- Asset labels
- Record labels

Services

- Service reminder

دیتاتک مرجع تخصصی خرید تجهیزات بارکد، کارتهای هوشمند و RFID

www.datatech.ir | info@datatech.ir | ۰۲۱ ۸۸۳۱۷۷۳۴



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
+1 847 955 2283
la.contactme@zebra.com